

Upright freezer LT U250



- Optimal footprint
- Low cost of ownership
- Limited maintenance and On-site service
- Easily installable & movable
- Eco-friendly, HCFC-free Nature R refrigerant
- Efficient cyclopentane insulation
- Low energy consumption
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications	
Technical	
Gross volume	253 litres
Net Volume	236 litres
Temp. range	-10°C to -45°C
Temperature probes	1
Compressor type	Secop
Refrigerant	Nature R
Noise level	60 dB
Power consumption 24/h	5,5 kWh
Power consumption	2.008 kWh / year
Voltage	220V-240V
Frequency	50 Hz
Features	
Castors with brakes	4
Inner doors	0
Defrost	Manual
Battery Backup	50h
USB	YES
Data connection	MODBUS
Digital controller with display	XW737K
Data logging	35.000 Entries
High/Low temperature alarm	YES
Analogue chart recorder	Optional
Adjustable shelves, stainless	5
Door vacuum release	Automatic
Porthole for external probe	YES
Outer dimensions	
Height	1985 mm
Height w. castors	2055 mm
Width	600 mm
Depth	580 mm
Gross weight	125 kg
Net weight	112 kg
Inner dimensions	
Height	1420 mm
Width	420 mm
Depth	370 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %
Product no.	N121002



Storage capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	4 x 2 = 8	3	24	N321200
	5 x 2 = 10	12	120	N321210
			= 144	
75 mm	2 x 2 = 4	3	12	N321300
	3 x 2 = 6	12	72	N321310
			= 84	
100 mm	2 x 2 = 4	15	60	N321400