

Chest freezer XLT C400



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable
- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications

Technical

Gross volume	383 litres
Net Volume	368 litres
Temp. range	-30°C to -60°C
Temp. probes	1/PT 1000
Compressor type	Embraco
Baskets (incl./optional)	4/11
Refrigerant	Nature R
Noise level	55 dB
Power consumption 24/h	7,7 kWh
Power consumption	2.811 kWh / year
Voltage	220V-240V
Frequency	50 Hz

Features

Audible and visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Prepared for external logging equipment	YES

Material

Inner	Precoated white steel
Outer	Galvanized pre-coated steel

Outer dimensions

Height	850 mm
Height w. castors	890 mm
Width	1560 mm
Depth	695 mm
Net weight	88 kg

Inner dimensions

Height	635/385 mm
Width	1190/210 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

XLT C400



Product no.

N112004

Storage capacity

Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	6	3	18	N311200
	11	24	264	N311220
			= 282	
75 mm	4	3	12	N311300
	8	24	192	N311320
			= 204	
100 mm	3	3	9	N311400
	5	24	120	N311420
			= 129	