

L130

Technical data sheet

CFC / HCFC free:	yes
Climate class:	SN
Ambient temperature range °C (°F):	from +10 to +32 (from 50 to 90)
Max. relative humidity:	75%
Voltage V:	220-240
Frequency Hz:	50/60
Fuse Amp:	8
Power W:	200
Running current A:	1.0
Energy consumption Kwh/24h:	1.0 @50Hz / 1.0 @60Hz
Heat ejection Kcal/h:	36
Running time %:	17
Noise level dB(A) (in 1m height +1m distance):	35 @50Hz / 36 @60Hz
Accu data / function time:	12V -2.3 AH / 48 hours
Defrosting technique:	natural
Compressor manufacturer:	Secop
Compressor type:	NLE9KTK
Cooling capacity W (ASHRAE):	131
Capillary tube, inner diam x length mm (inch):	0.83 x 2050 (0.033 x 80.71)
Refrigerant type:	R600a
Refrigerant quantity g (oz):	23 (0.811)
Door insulation mm (inch):	82 (3.23)
Cabinet insulation mm (inch):	60 to 65 (2.36 to 2.56)
K value W/m ² xK at 20°C (68°F):	
Hold over time h at °C (°F):	1.5 from +5 to +10°C (from 41 to 50°F), DIN58345 @25°C (77°F)
Net volume l (cu ft):	106 (3.743)
Gross volume l (cu ft):	121 (4.273)
Internal width mm (inch):	475 (18.70)
Internal depth mm (inch):	470 (18.50)
Internal height mm (inch):	630 (24.80)
Internal height for usage mm (inch):	500 (19.69)
External width mm (inch):	595 (23.43)
External depth mm (inch):	695 (27.36)
External height mm (inch) [with recorder]:	830 (32.68) [1003 (39.49)]
Net weight with standard equipment kg (lbs):	59 (130.07)
EMC standards:	IEC 61326-1
Safety standards:	IEC 61010-1 / IEC 61010-2-011
Medical Device Regulation:	(EU) 2017/745: Class I
GMP-clean room classification:	class ISO6/EC GMP B
ATEX / IECEx marking:	Not applicable

Subject to changes without prior notice !

Revision: 29/04/2020

Measurement conditions:

**Setpoint +5°C (41°F) @ +25°C (77°F) ambient temperature, unless otherwise stated
All appliances without load**