

L500

Technical data sheet

CFC / HCFC free:	yes
Climate class:	SN / T
Ambient temperature range °C (°F):	from +10 to +43 (from 50 to 109.4)
Max. relative humidity:	75%
<hr/>	
Voltage V:	220-240
Frequency Hz:	50/60
Fuse Amp:	8
Power W:	300
Running current A:	1.2
Energy consumption Kwh/24h:	1.40 @50Hz / 1.40 @60Hz
Heat ejection Kcal/h:	33
Running time %:	25
Noise level dB(A) (in 1m height +1m distance):	47 @50Hz / 51 @60Hz
Accu data / function time:	12V -7.0 AH / 48 hours
Defrosting technique:	natural
<hr/>	
Compressor manufacturer:	Secop
Compressor type:	NLE9KTK
Cooling capacity W (ASHRAE):	131
Capillary tube, inner diam x length mm (inch):	0.90 x 3000 (0.035 x 118.11)
Refrigerant type:	R600a
Refrigerant quantity g (oz):	50 (1.764)
<hr/>	
Door insulation mm (inch):	65 to 82 (2.56 to 3.23)
Cabinet insulation mm (inch):	77 to 82 (3.03 to 3.23)
K value W/m ² xK at 20°C (68°F):	
Hold over time h at °C (°F):	1.6 from +5 to +10°C (from 41 to 50°F), DIN58345 @25°C (77°F)
<hr/>	
Net volume l (cu ft):	510 (18.011)
Gross volume l (cu ft):	598 (21.118)
Internal width mm (inch):	590 (23.23)
Internal depth mm (inch):	713 (28.07)
Internal height mm (inch):	1167 (45.95)
Internal height for usage mm (inch):	1150 (45.28)
External width mm (inch):	845 (33.27)
External depth mm (inch):	1039 (40.91)
External height mm (inch):	1988 (78.27)
Net weight kg (lbs) (with standard equipment):	215 (474.00)
<hr/>	
EMC standards:	IEC 61326-1
Safety standards:	IEC 61010-1 / IEC 61010-2-011
Medical Device Regulation:	(EU) 2017/745: Class I
GMP-clean room classification:	class ISO5/EC GMP A
ATEX / IECEx marking:	Not applicable

Subject to changes without prior notice !

Revision: 29/04/2020

Measurement conditions:

**Setpoint +5°C (41°F) @ +25°C (77°F) ambient temperature, unless otherwise stated
All appliances without load**